

FYL- 4354UWC1A


Features:

- High intensity
- General purpose leads
- RoHS Compliant.

Descriptions:

- Dice material: InGaN.
- Emitting Color: White
- Device Outline: 4*3 ellipse Type.
- Lens Type: Water clear

Radiation pattern.




Absolute maximum ratings(Ta=25 °c)

Parameter	MAX.	Unit
Power Dissipation	70	mW
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width)	100	mA
Continuous Forward Current	20	mA
Derating Linear From 50°C	0.4	mA/°C
Reverse Voltage	5	V
Electrostatic Discharge (ESD)	150	V
Operating Temperature Range	-30°C to +80°C	
Storage Temperature Range	-40°C to +100°C	
Lead Soldering Temperature[4mm(.157") From Body]	260°C for 5 Seconds	

Electrical and optical characteristics(Ta=25 °c)






Parameter	Symbol	Min.	Typ.	Max.	Unit	Test Condition
Luminous Intensity	I _V		2800		mcd	I _F =20mA
Viewing Angle	2θ _{1/2}	X	70	80	90	
		Y	35	40	45	
Chromaticity coordinates	x		0.29			
	y		0.30			
Forward Voltage	V _F	2.8	3.2	3.6	V	V _R =5V
Reverse Current	I _R			50	μA	

Package configuration




- ◆ All dimensions are millimeters (inches)
- ◆ Tolerance is ±0.25mm(.010") unless otherwise noted.

Typical Electrical Characteristics Curves (25 °c Ambient Temperature Unless Otherwise Noted)




LAMP PACKING.



DEVICE	QTY/polybag(pcs)	Polybag/box A	Fig
5mm(T-1 3/4)	1000	8 bags	Label 1
3mm(T-1)	1000	10 bags	Label 1
10mm(T-1)	250	8 bags	Label 1
Blue/Green/White	500pcs	8 bags	Label 2

CARTON
Dimension(cm):39*32*38



6 Boxes/Carton
 5mm:48,000pcs
 3mm:60,000pcs
 10mm:12,000pcs
 Blue/Pure Green/bluish Green
 /White:24,000pcs